



## Copper Utility Coils

Copper Utility Tubing, O60 (Soft Annealed Temper, .040 mm min. Grain Size)  
 UNS C12200 DHP Copper Alloy per ASTM B 68, B 75

10', 15', 20' and 50' Lengths in Single and or Double Layer form dependant on OD and Length



*Individually Bagged*



*Boxed for Distribution*



*Bulk Packed for Processing*



*Bulk Packed in Sealed Bags*

Individually bagged with plain or pre-printed artwork, packed in custom 10-pack boxes with UPC tags and loaded on a skid with stretch wrap film. Available in bulk form as well.

**Size Range Chart I 3/16" to 3/8" O.D.**

**Size Range Chart II 1/2" to 3/4" O.D.**

OD Size (inches)	Wall	Wt./Ft.	Coil Length (feet)	Wt./Pc.	Coil Style	OD Size (inches)	Wall	Wt./Ft.	Coil Length (feet)	Wt./Pc.	Coil Style
3/16	.016/.020	.03342	10	.3342	Single Layer	1/2	.020/.024	.1169	10	1.17	Single Layer
3/16	"	"	15	.5013	"	1/2	"	"	15	1.75	"
3/16	"	"	20	.6684	"	1/2	"	"	20	2.34	"
3/16	"	"	25	.8355	Double Layer	1/2	"	"	25	2.92	Double Layer
3/16	"	"	50	1.67	"	1/2	"	"	50	5.85	"
1/4	.018/.022	.05086	10	.5086	Single Layer	5/8	.022/.026	.1686	10	1.69	Single Layer
1/4	"	"	15	.7629	"	5/8	"	"	15	2.53	"
1/4	"	"	20	1.02	"	5/8	"	"	20	3.37	Double Layer
1/4	"	"	25	1.27	Double Layer	5/8	"	"	25	4.21	"
1/4	"	"	50	2.54	"	5/8	"	"	50	8.43	"
3/8	"	.07828	10	.7827	Single Layer	3/4	.024/.028	.2293	10	2.29	Single Layer
3/8	"	"	15	1.17	"	3/4	"	"	15	3.44	"
3/8	"	"	20	.152	"	3/4	"	"	20	4.58	Double Layer
3/8	"	"	25	1.96	Double Layer	3/4	"	"	25	5.73	"
3/8	"	"	50	3.91	"	3/4	"	"	50	11.46	"

Dayco Industries can also provide saddle valves (Self-piercing and non-self piercing) for each size of utility tubing along with any of the Copper and or Brass Fittings which would be associated to the use of the utility coil by the end user. Custom sizes and lengths can be quoted upon request.

**Dayco Industries, LLC • 10215 San Sevaine Way • Mira Loma, CA 91752**  
 Call Toll Free: (800) 893-8355 • Local: (951) 360-5900 • Fax: (951) 360-6198  
 E-mail: [Sales@daycoindustries.com](mailto:Sales@daycoindustries.com)